



TOTAL INGENIEROS S.A.C
VENTAS, PROYECTOS, SERVICIOS EN INGENIERÍA Y SISTEMAS DE REFRIGERACIÓN

HONGSEN 鸿森

2021-2022

制冷空调系统配件

REFRIGERATION A/C SYSTEM ACCESSORIES

HONGSEN MACHINERY
Escort For Safe Refrigeration

REFRIGERATION A/C SYSTEM ACCESSORIES

制冷空调系统配件



HONGSEN® 鸿森®

浙江鸿森机械有限公司
ZHEJIANG HONGSEN MACHINERY CO.,LTD
地址: 浙江省诸暨市店口镇制冷工业园区
Address: Diankou refrigeration industrial park, Zhuji city, Zhejiang province
电话 /Tel: 0575-87696107/0575-87607883/0575-87608106
传真 /Fax: 0575-87698985 PostCode:311802
E-mail: hongsen@zhsjx.com;hongsen6@zhsjx.com;zhongsen@163.com

HONGSEN

MANIFOLD GAUGE SET

Digital manifold HS-330



Technical Parameters

Pressure value: gauge pressure

Pressure unit: Kpa; MPa; bar; inHg; Psi

Pressure range: 0Kpa~6000Kpa

Accuracy: $\pm 0.5\%$ (FS)+5dgt

Overload Pressure limit: 10000Kpa (10MPa; 100bar)

Temperature unit: °C/°F

Temperature range: -40°C~-150°C (-40°F~-302°F)

Temperature accuracy: $\pm 0.5^\circ\text{C}+2\text{dgt}$ $\pm 0.9^\circ\text{F}+2\text{dgt}$

Power Supply: 4×1.5V

Connector: 1/4SAE

Vacuum value: relative vacuum

Vacuum unit: Kpa; MPa; bar; inHg; Psi

Vacuum range: -101Kpa~0Kpa

Refrigerant(89):R11 R113 R114 R115 R116 R12 R123 R124 R125 R1270
R13 R134A R14 R141B R142B R143A R152A R170 R21 R218 R22 R2270A
R23 R236EA R245CA R245FA R290 R32 R401A R401B R401C R401A R402B
R403A R403B R404 R405A R405A R407A R407B R407C R407D R407E R408A
R409A R409B R41 R410A R410B R411A R411B R412A R413A R414A R414B
R415A R415B R416A R417A R418A R419A R420A R421A R421B R422A
R422B R422C R422D R423A R424A R425A R426A R427A R428A R50 R500
R501 R502 R503 R504 R507A R508A R508B R509A AR600 R600A R717 R744
(Co2) 1234yf

Product Characteristics

- High-strength engineering plastics applied for the housing, make it strong and solid.
- Flexible non-slip silicone design, comfortable to hold.
- High-precision data acquisition unit, stable and accurate.
- Backlight design, easy to operate in low light.
- Micro-power electronics, to extend battery life.
- Built-in 89 kinds of refrigerant database, complete parameters.
- Dual-channel real-time temperature measurement, accurate and convenient.
- Multi-mode selection, full-featured.
- Folding hook, easy to storage.
- High-quality aluminum alloy valve manifold, durable.
- Explosion-proof sight glass, safe and reliable.