



TOTAL INGENIEROS S.A.C
VENTAS, PROYECTOS, SERVICIOS EN INGENIERIA Y SISTEMAS DE REFRIGERACIÓN

Industrial Refrigeration Control Components



Dofun

Atlas For Selecting Models


山东东阀制冷科技有限公司
Shandong DoFun Refrigeration Technology Co., Ltd

山东东阀制冷科技有限公司


1、技术参数 Technical Parameter

- ◆ 公称通径：DN15-DN200
Nominal Diameter: DN15-DN200
- ◆ 公称压力：4.0MPa
Nominal Pressure: 4.0MPa
- ◆ 适用介质：R12,R22,R502,R134a,R404a,R507,R717等制冷剂。
Applicable Medium: R12, R22, R502, R134a, R404a, R507, R717 and other refrigerants.


- ◆ 适用温度：-46℃~+150℃
Applicable Temperature: -46℃ ~ +150℃
- ◆ 滤网规格有150目、100目、72目、38目，可以根据不同的管路系统要求选配。
The specifications of the filter screen are 150 mesh, 100 mesh, 72 mesh, 38 mesh, which can be selected according to the requirements of different pipeline.




对接焊图示 BW



承插焊图示 SOC



对接焊图示 BW



承插焊图示 SOC

角式过滤器 Angle Type Filter					
型号 Model	Nominal Diameter	通径 尺寸Size (mm)			
		(DN) H1	H2	L1	L2
	15	115.5	115.5	45	120
	20	115.5	115.5	45	120
	25	115.5	119.5	45	120
	32	141.5	147.5	49.5	156
	40	141.5	147.5	56	156
	50	130	135	60	162
	65	148 / 70			/
	80	224 / 106			/
	100	253 / 121			/
	125	273.5 / 133			/
	150	311 / 146			/
	200	380.5 / 180			/

直通过滤器 Straight Type Filter					
型号 Model	Nominal Diameter	通径 尺寸Size (mm)			
		(DN) H1	H2	L	L2
	15	103	103	120	120
	20	103	103	120	120
	25	103	107	120	120
	32	131	135	128	156
	40	131	135	156	156
	50	140	145	149	162
	65	164 / 176			/
	80	215 / 216			/
		100	261 / 264		/
		125	316 / 330		/
		150	371 / 370		/
		200	485 / 460		/